10/537770

JC17 Rec'd PCT/PTO 06 JUN 2005

Applicant(s): Graham Paul HOPKINS et al. Atty. Docket: 41557-218983 RK

IN THE CLAIMS:

Prior to examination on the merits, please amend the claims of the international

application as follows.

1. (Original) A gas sensor comprising a body, on which is mounted an optical source and

detector means sensitive to light from the source, the body further comprising a channel arranged to

admit gas, the channel comprising an elongated groove having reflective surfaces defining a folded

optical path for light from the source.

2. (Original) A sensor as claimed in claim 1, in which the source is located at one end portion

of the channel.

3. (Original) A sensor as claimed in claim 2, in which the detector means comprises a first

detector located at the other end portion of the channel.

4. (Original) A sensor as claimed in claim 3, in which the detector means further comprises a

second detector, the sensor further comprising means arranged to redirect a portion of light from a

predetermined region of the channel to the second detector.

5. (Currently Amended) A sensor as claimed in any previous claim 1, in which a portion of the

elongated groove forms a spiral optical path.

6. (Currently Amended) A sensor as claimed in any previous claim 1, in which a portion of the

groove forms a serpentine optical path.

7. (Currently Amended) A sensor as claimed in any previous claim 1, in which a portion of the

groove forms a helical optical path.

- 2 -

Applicant(s): Graham Paul HOPKINS et al.

Atty. Docket: 41557-218983 RK

8. (Original) A sensor as claimed in claim 7, in which the body is cylindrical and the helical

optical path extends around the exterior of the body.

9. (Original) A sensor as claimed in claim 8, in which the cylinder includes a hollow region and

a portion of the groove comprises a helical optical path around the interior of the hollow region.

10. (Original) A sensor as claimed in claim 7, in which the body includes a hollow cylindrical

region and a portion of the groove comprises a helical optical path around the interior of the hollow

region.

11. (Currently Amended) A sensor as claimed in any one of claims claim 1 to 7, in which the

body comprises a base arranged to accommodate the source and detector(s) and at least one wall

extending transversely from the plane of the base.

12. (Original) A sensor as claimed in claim 11, in which the walls are arranged substantially to

bisect each other transversely.

13. (Currently Amended) A sensor as claimed in claim 11 or 12, in which a portion of the

elongated groove is located on the at least one wall and a portion of the groove is located on the base.

14. (Currently Amended) A sensor as claimed in any previous claim 1, further comprising a

cover for the channel including gas admittance means.

15. (Original) A sensor as claimed in claim 14, in which the cover has an interior surface facing

the channel, which surface is arranged to reflect radiation.

16. (Currently Amended) A sensor as claimed in claim 14 or 15, in which the gas admittance

means includes sintered material.

- 3 -

Applicant(s): Graham Paul HOPKINS et al. Atty. Docket: 41557-218983 RK

17. (Currently Ameneded) A sensor as claimed in claim 14 or 15, in which the gas admittance

means includes a particulate filter.

18. (Currently Amended) A sensor as claimed in any preceding claim 1 wherein the optical

source is an infrared source.

19. (Cancelled) A gas sensor, substantially as hereinbefore described, with reference to, or as

illustrated in, the accompanying drawings.